

RELLIK

HIGH
LIVING
COLLECTIONS

FLOOR AND WALL
TILES by

APAVISA

DIRECTORY	
Ballroom Salons	Floor 1
The Board Room	Floor 3
Fitness Center	Floor 14
The Gallery Room	Floor 1
Logic Room	Floor 3
Pool	Floor 14
Strategy Room	Floor 3



Floor: RELLIK Grey Natural 100x100



floor: RELLIK White Natural 50x100



garden: RELLIK Beige Solid 2CM

ELEGANCE BY NATURE.
LA ELEGANCIA POR
NATURALEZA.



walls: ONICE Salmon Decor 45x120
floor: RELLIK Beige Lappato 100x100

COLORS & FINISHES



Beige



	100x100 (7 mm)	(99.55 x 99.55 cm - 39.19"x39.19")
	RELLIK Beige Natural 100x100	G-1268
	RELLIK Beige Lappato 100x100	G-1298
	50x100 (7 mm)	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK Beige Natural 50x100	G-1220
	RELLIK Beige Lappato 50x100	G-1250
	60x60 (7 mm)	(59.55 x 59.55 cm - 23.62"x23.62")
	RELLIK Beige Natural 60x60	G-1220
	SOLID 2CM	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK Beige Natural SOLID 2CM	G-1234



White



	100x100 (7 mm)	(99.55 x 99.55 cm - 39.19"x39.19")
	RELLIK White Natural 100x100	G-1268
	RELLIK White Lappato 100x100	G-1298
	50x100 (7 mm)	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK White Natural 50x100	G-1220
	RELLIK White Lappato 50x100	G-1250
	60x60 (7 mm)	(59.55 x 59.55 cm - 23.62"x23.62")
	RELLIK White Natural 60x60	G-1220
	SOLID 2CM	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK White Natural SOLID 2CM	G-1234




Grey



	100x100 (7 mm)	(99.55 x 99.55 cm - 39.19"x39.19")
	RELLIK Grey Natural 100x100	G-1268
	RELLIK Grey Lappato 100x100 VVV	G-1298
	50x100 (7 mm)	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK Grey Natural 50x100	G-1220
	RELLIK Grey Lappato 50x100	G-1250
	60x60 (7 mm)	(59.55 x 59.55 cm - 23.62"x23.62")
	RELLIK Grey Natural 60x60	G-1220
	SOLID 2CM	(49.75 x 99.55 cm - 19.59"x39.19")
	RELLIK Grey Natural SOLID 2CM	G-1234

Non-slip values
Valores antideslizamiento

	NATURAL		DIN: R10		PTV: >36		CLASE: 1				
			DIN 51130		BS-7976		UNE 41901 EX				
	LAPPATO		DIN: R10		PTV: >36		CLASE: 1				
			DIN 51130		BS-7976		UNE 41901 EX				
	SOLID 2 cm		DIN: R11		CLASS: C		DCOF: >0,42		PTV: >36		CLASE: 3
			DIN 51130		DIN 51130		ANSI A 137.1		BS-7976		UNE 41901 EX

PACKING	Size cm	Size “	Box/ Pallet	Pzs/ Box	M2/ Pallet	M2/ Box	SQF/ Pallet	SQF/ Box	Kg/ Pallet	Kg/ Box	Kg/ Piece
100x100 (7 mm)	99,55x99,55	39.19X39.19	24	2	47,569	1,982	512,032	21,335	822	32,750	16,200
50x100 (7 mm)	49,75x99,55	19.59X39.19	27	4	53,488	1,981	575,747	21,324	917	33,095	8,200
60x60 (7 mm)	59,55x59,55	23.44X23.44	30	5	53,193	1,773	572,570	19,086	950	30,898	6,129
SOLID 2CM (20mm)	49,75x99,55	19.59X39.19	36	1	17,829	0,495	191,916	5,331	825	22,362	22,067

RELLIK

HL

HIGH LIVING COLLECTIONS

FLOOR AND WALL TILES

SYMBOLS / SÍMBOLOS

FINISHES / ACABADOS



NATURAL
NATURAL



LAPPATO
LAPPATO



POLISHED
PULIDO



SATIN
SATINADO



STRUCTURED
ESTRUCTURADO



SHINY
BRILLO



MATT
MATE



METAL
METALIZADO



RELIEF
RELIEVE



NON SLIP
ANTIDESLIZANTE

CLEANING AND MAINTENANCE TIPS

THE FIRST CLEANING “AFTER INSTALLATION”

The most important cleaning operation is performed immediately after laying the tiles. This involves the complete removal of residues and dirt from the tile placement. An inadequate or late removal of this waste can create a cementitious layer on the tile capable of absorbing all forms of dirt. This may give the impression that the tile gets dirty when the actual problem resides in the surface film of dirt which was not removed immediately after laying. Once the grouting of the tiles is finished, it is important, while the grout is still wet, to carefully remove any excess material immediately. This can be done using a sponge and plenty of clean water, repeating this as many times as necessary. Do not perform the cleaning with metal tools, scrapers or abrasive pads. For stubborn stains, clean with alcohol and lukewarm water and rub with a clean cloth. If they do not disappear, check with the relevant technical department. Once the above mentioned washing is done, another washing should be carried out using basic or alkaline degreasing agents, as acid washing can leave stickiness on the pavement which could help retain dirt. In areas where water is calcareous, it is convenient to dry the surface, in order to prevent the deposition of carbonates which will reduce the surfaces' gleam.

REGULAR MAINTENANCE

Many available cleaning products for general use can be used with our products. For daily cleaning, one can use detergents or degreasing products diluted in warm water, following each product's instructions. It is important that the cleaner does not have oil, animal fat, or soap base. These components may leave an invisible residue whilst absorbing dirt (lime stratifications detergent or residues). It is also important that the tile receives a thorough rinsing with clean water after the cleaning process is complete. The low water absorption and high standards met by all porcelain tiles ensure a product which is easy to maintain. Our products do not require the use of sealants or waxes. These superficial coatings can really affect the performance of the tile in a negative manner. It is important to note that hydrofluoric acid (HF) and derivatives can irreparably damage the tile. The general steps for regular cleaning of our ceramic products can be summarized as follows:

- Remove any solid or liquid waste from the tile, sweeping with a soft bristle broom or vacuuming.
- Clean up liquid spills as soon as possible with lukewarm water.
- Apply the recommended amount and dilution of the cleaner for the tile (follow the cleaner manufacturer's instructions). The wiper must remain in the tile a minimum period of 5 minutes.
- For unpolished tiles, scrub with a nylon sponge or soft bristle brush. A floor machine equipped with a nylon pad or bristle brush can be used for heavily soiled surfaces. For polished tiles, clean with a nonabrasive cloth.
- Remove the dirty cleaning solution and water with a vacuum cleaner or cloth. Rinse the porcelain tile with clean water and remove again with a vacuum cleaner, mop or towel. It is absolutely essential that all detergent residues are removed completely from the tile. Any remaining detergent that dries on the tiles surface can form a coating that can trap dirt and be very difficult to remove. The tile should be rinsed several times to remove all detergent residues.

During use, the cleaning of the tiles should be similar to window cleaning. Ammonia and even bleach type products can be employed, but both must be diluted in water.

In case of special stains and/or particularly resistant, it is advisable to use specific detergents according to the cleaners' manufacturer. Do not forget that removing any type of stain is easier when it is still fresh. It is important to always do a pre-test the detergent products result on a small sample of the porcelain.

CONSEJOS DE LIMPIEZA Y MANTENIMIENTO

LA PRIMERA LIMPIEZA DESPUÉS DE LA COLOCACIÓN

La operación de limpieza más importante se lleva a cabo inmediatamente “después de la colocación de la baldosa”. Esto implica la eliminación completa de los residuos de lechada y de la suciedad de la colocación de las propias baldosas. Una eliminación inadecuada o tardía de estos residuos puede crear sobre la baldosa una película cementosa capaz de absorber toda forma de suciedad, dando la impresión que se ensucia la baldosa, cuando el problema está en la película superficial de suciedad. Una vez efectuado el rejuntado de las baldosas, es importante cuando el material de rejuntado todavía está fresco, eliminar el material sobrante cuidadosa e inmediatamente, utilizando para ello una esponja y agua limpia abundante, repitiendo esta operación tantas veces como sea necesario. No debe realizarse la limpieza del material con espátulas metálicas ni estropajos abrasivos. En el caso de manchas resistentes, limpiar con alcohol y agua caliente y frotar con un paño limpio. Si no desaparecen, consultar con el departamento técnico correspondiente. Una vez efectuado el lavado mencionado arriba, deberá efectuarse un lavado básico o alcalino utilizando detergentes desengrasantes, ya que el lavado ácido puede dejar una untuosidad sobre el pavimento que podría contribuir a retener la suciedad. En aquellas zonas donde el agua sea calcárea conviene secar la superficie para evitar la deposición de carbonatos que disminuyen el brillo superficial.

EL MANTENIMIENTO REGULAR

Muchos productos de limpieza de uso general que están disponibles son aceptables para el uso en nuestros productos. Se puede emplear para la limpieza diaria detergentes o desengrasantes diluidos en agua caliente, según indicaciones del envase del limpiador. La densidad inherente y baja absorción de agua de todos los productos aseguran un producto que es fácil de mantener. Es muy importante tener en cuenta que el ácido Fluorhídrico (HF) y derivados pueden dañar irremediablemente la baldosa.

Los pasos generales de limpieza regular para nuestros productos cerámicos se pueden resumir del siguiente modo:

- Retirar cualquier residuo sólido o líquido de la baldosa, barriendo con una escoba de cerdas suaves o pasar la aspiradora.
 - Limpiar los derrames líquidos tan pronto como sea posible.
 - Aplicar la cantidad y dilución del limpiador recomendadas para la baldosa (ver indicaciones del fabricante del limpiador). El limpiador deberá permanecer en la baldosa un periodo mínimo de tiempo de 5 minutos.
 - Para baldosas sin pulir, frotar con una esponja de nylon o un cepillo de cerdas suaves. Para superficies muy sucias puede usarse una máquina de piso equipado con una almohadilla de nylon o con un cepillo de cerdas. Para baldosas pulidas, limpie con un trapo no abrasivo o un paño.
 - Retirar la solución de limpieza sucia y el agua con una aspiradora o un trapo. Enjuague la pieza con agua limpia y retire de nuevo con una aspiradora, fregona, o una toalla. Es absolutamente esencial para todos los residuos de detergente que se eliminen por completo de la baldosa. Cualquier resto de detergente que se seque sobre la baldosa puede formar un recubrimiento que puede atrapar la suciedad y será muy difícil de eliminar. La baldosa debe enjuagarse varias veces para eliminar todos los residuos de detergente.
- Durante su uso, la limpieza de la baldosa debe hacerse de forma similar a la limpieza de cristales. Se puede emplear productos de tipo amoniacal e incluso lejía, ambos diluidos en agua.

En caso de manchas particulares y/o especialmente resistentes, es aconsejable usar detergentes específicos según especificaciones del fabricante del limpiador. No hay que olvidar que la eliminación de cualquier tipo de mancha resulta más fácil cuando ésta todavía está fresca.

Es importante hacer siempre una prueba previa antes de usar los productos detergentes.



APAVISA

APAVISA PORCELANICO S.L. assumes no liability for any printing errors. The technical characteristics contained in this catalog are mean values of our products. To carry out any orders that are requested consultations with the technical characteristics of the particular model to APAVISA PORCELANICO S.L.

All features and specifications are based on information available at the time of printing this catalog and may be changed without notice, according to market conditions, technological innovations and / or any other factor, without incurring any liability.

APAVISA PORCELANICO S.L. no asume ninguna responsabilidad por posibles errores de impresión. Las características técnicas que constan en el presente catálogo son valores medios de nuestros productos. Para la realización de cualquier pedido se solicita que sean consultadas las características técnicas del modelo en concreto a

APAVISA PORCELANICO S.L.

Todas las características y especificaciones técnicas están basadas en la información disponible en el momento de la impresión del presente catálogo y podrán ser modificadas sin previo aviso, de acuerdo a las circunstancias del mercado, innovaciones tecnológicas y/o cualquier otro factor, sin incurrir en ningún tipo de responsabilidad.

RELLIK

FLOOR AND WALL
TILES

APAVISA

www.apavisa.com



Ctra. Castellón – San Juan de Moró, hm.7,5 - 12130 SAN JUAN DE MORÓ (Castellón) Spain
Tel. +34 964 701 120 - Export Fax +34 964 701 067 - Fax Nacional 964 701 195 - info@apavisa.com