

Hurricane 2.0



Gres in massa
Rettificato - Rectified - Rectifié - Rektifiziert

UNI EN 14411 - G Bla



60x120 cm
± 20 mm

In alto: Pav Esterno_Hurricane 2.0 Silver
Riv_Pietre Bianco
In basso: Silver
A destra: Smoke




Hurricane p. 44



Hurricane p. 228

Hurricane 2.0



CLOUD
0447074 60x120



SILVER
0447057 60x120



COAL
0447075 60x120



SMOKE
0447058 60x120

Hurricane 2.0

PEZZI SPECIALI / Special pieces / Pièces spéciales / Formteile



30x120x2
GRADONE STEP

Pc. Box	3
CLOUD	0447139
SILVER	0447069
COAL	0447140
SMOKE	0447141

Vendita solo a scatole complete / To be sold as full box only / Vendable uniquement en boites entières / Abnahme nur volle Pakete.



CERTIFICAZIONE / Certification / Certification / Zertifizierung

CARATTERISTICHE TECNICHE / Technical features / Caractéristiques techniques / Technische Eigenschaften

Scivolosità: Metodo della rampa calzato \ Skid resistance: Shood Ramp Test	Scivolosità: Metodo della rampa a piedi nudi / Skid resistance: Barefoot Ramp Test	Scivolosità: Metodo del pendolo / Skid resistance: Pendolum Friction Test	Scivolosità: Coefficiente di attrito / Skid resistance: Coefficient of Friction (COF)	Scivolosità: Coefficiente di attrito dinamico / Skid resistance: Dynamic Coefficient of friction (DCOF)
R11	C	Class C3	> 0,40 Dry > 0,40 Wet	> 0,42 Wet

IMBALLI / Packages / Emballages / Verpackungen

	SCATOLE / Boxes / Boites / Kartons			PALETTE / Pallets / Palettes / Paletten			+ mm
	pz.	m ^q	kg	box	m ^q	kg	
60x120	1	0,72	33,1	30	21,6	993	20