



# OKLAHOMA


20X120 — 7,87"X47,24"




Porcelánico  
Porcelain




Polivalente  
Versatile




Mate  
Matt




Muy Dest. (v4)  
Shade Variation: High




No Repetitivo  
No Repetitive




Relieve  
Relief



Antihielo  
Frost proof



Rectificado  
Rectified



R10  
R10



OKLAHOMA HAYA  
P2012L



OKLAHOMA CENIZA  
P2012L



OKLAHOMA NOGAL  
P2012R

## CARACTERÍSTICAS TÉCNICAS / TECHNICAL CHARACTERISTICS

Formato Size		Color Colour	MOHS (Dureza) Strength Resistance	PEI		DESLIZAMIENTO GLIDE			Absorción de Agua Water Absorption	Resistencia Química / Chemical Resistance								Resistencia a las Manchas Stain Resistance			Resistencia Mecánica Mechanical Resistance	
										Clase Class	Etap Abrasión Abrasion Stage	P.D. Limpieza Cleaning	Aditivos Agua Piscina Additive pools water	Ácidos y Alcalis Acids and Alkalies (Baja concentración) (Low concentration)			Ácidos y Alcalis Acids and Alkalies (Alta concentración) (High concentration)					
				UNE-ENV 12633:2003	DIN 51130**									DIN 51097**	Cloruro Amónico. Ammonia Chloride	Ácido Cloríd. Citric Acid	Hidróxido Potásico Potassium Hydroxide					
				PÉNDULO PENDULUM	RAMPA RAMP	PIE DESCALZO BARE FOOT																
20X120	Haya	6	4	6000	2	R10		<0,5%	GA	GA	GLA	GLA	GLA	GHA	GHA	GHA	5	5	5	RESISTE	>35N/mm2	
	Ceniza	6	4	6000	2	R10		<0,5%	GA	GA	GLA	GLA	GLA	GHA	GHA	GHA	5	5	5	RESISTE	>35N/mm2	
	Nogal	6	3	1500	2	R10		<0,5%	GA	GA	GLA	GLA	GLA	GHA	GHA	GHA	5	5	5	RESISTE	>35N/mm2	

## EMBALAJE / PACKING LIST

	Pcs / Cajas Pcs / Box	M2 / Cajas Sq. / Box (aprox.)	Kg / Cajas Kg / Box	Cajas / Palet Boxes / Pallet	M2 / Palet Sq. / Pallet (aprox.)	Kg / Palet Kg / Pallet	Pulgadas Inches
20X120	4	0.96	22.5	48	46.08	1080	7,87"X47,24"



Se aconseja uso del Sistema Nivelado  
We recommend using Levelling System to fix the tiles

: 15/07/2019

BALDOCER