



398

399

# FS Star

Single fired floor tiles



FS Star-N





400

401

# FS Star

Single fired floor tiles



FS Star-N





# FS Star

Single fired floor tiles

FS Star Oxide  
FS 0



FS STAR Blue



FS STAR Oxide




FS STAR Sage




FS STAR N

## FS STAR



45 \* 45 \* 1,05 cm | 18 \* 18"

NO RECTIFIED	NATURAL PRICE CODE BN14
BLUE	23200
OXIDE	23198
SAGE	23199
N	19136



Rodapie - Skirting (R. FS 0)  
8 \* 45 cm | 3 \* 18" PB

CARACTERÍSTICAS TÉCNICAS   TECHNICAL CHARACTERISTICS		
joint 1,5 mm	versatile	mat
diferent shades	shade variation	various graphics

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO   ANTI-SLIP CHARACTERISTICS		
Ensayo   Essay	Características   Features	Resultado   Result
DIN 51130	Ángulo crítico (Pies calzados)   Critical angle (footwear)	R9
BS 7976-2	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test-PTV)	+36 Wet
UNE-ENV 12633	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	Class 1
ANSI A.1371	Coefficiente de Fricción Dinámico   Dynamic Coefficient of Friction (DCOF)	>0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/Resistance to Surface Abrasion	PEI 4

EMBALAJE   PACKING		(Los pesos aquí reflejados pueden sufrir ligeras variaciones en función del lote de producción. Weights shown here may slightly vary depending on the production lot.)							
Formato   Sizes	Cajas   Boxes	Pallet						Cont./20' 21500 kg.	Cont./20' 24000 kg.
cm	Piezas m <sup>2</sup> / sq.m kg	Cajas	m <sup>2</sup> / sq.m	kg	Tamaño cm aprox.	m <sup>2</sup> / sq.m	m <sup>2</sup> / sq.m		
45 * 45 * 1,05	5 1 23,139	66	66	1551	120 * 80 * 105	914,89	1021,28		
inch	Units ft <sup>2</sup> lb	Boxes	ft <sup>2</sup>	lb	Sizes inch approx.	ft <sup>2</sup>	ft <sup>2</sup>		
17 11/16 * 17 11/16 * 7/16	5 10,76 51,02	66	710,42	3419,96	47 1/4 * 31 1/2 * 41 5/16	9847,91	10993,02		